



Symbol LS9203

Omni-directional presentation scanner



FEATURES

Electronic data capture technology

Eliminates manual effort and paper-based data collection errors, reducing costs related to inventory errors and shrinkage while also improving accuracy and speeding POS data collection

Omni-directional scan pattern

Speeds checkout times and frees employees to serve more customers

Flexible handheld or hands-free scanning

Saves employees time, lowers equipment costs and reduces injuries caused by heavy lifting

Durable design

Ensures reliable performance and investment protection by withstanding multiple drops to concrete

Improve operations with affordable advanced data capture

Easy to use, deploy and maintain, the Symbol LS9203 omni-directional presentation scanner from Motorola delivers a high-value choice for seamless integration of advanced data capture into your point-of-sale (POS) environment — at an affordable price. Designed to speed the checkout process for customers while improving sales tracking and inventory management, the Symbol LS9203 high-performance handheld and presentation scanning capability enables your POS employees to work faster and more accurately. And durable construction protects it from the shocks of heavy use, extending the life of your investment.

Reduce costs and streamline POS activity

The Symbol LS9203 helps you lower costs by eliminating the errors inherent with manual, paper-based sales and inventory tracking. You increase profitability by reducing pricing mistakes, minimizing shrinkage and providing better visibility into fundamental business processes. Because the Symbol LS9203 is both a handheld and a presentation scanner, your employees are able to quickly switch between hands-free and handheld mode to scan bar codes easily, maximizing their productivity. You also help reduce injuries, because your employees and customers don't

need to lift or maneuver heavy items for scanning. And the durable construction of the Symbol LS9203 means you'll avoid downtime resulting from equipment failure.

Use right out of the box

The Symbol LS9203 comes complete with cables, and in most cases, all you need to do is simply plug in the device. Any required customized configuration can be completed quickly and easily with a quick scan of a provided set of programming bar codes. Designed with multiple on-board interfaces and universal cables, the Symbol LS9203 provides flexible host connectivity and easy migration to new hosts — without requiring the replacement of scanners.

Enhance customer service

This easy-to-use scanner allows your employees to work more effectively with customers, no matter how long they've been on the job. Faster checkout, gives workers more time to assist customers. The small footprint leaves plenty of space at the register for "impulse purchase" displays to encourage additional sales. And, with the capability to more accurately track customer behavior, inventory management is improved, ensuring that the right product is stocked at the right time to protect against lost sales.

SPECIFICATION SHEET

SYMBOL LS9203
Omni-directional presentation scanner

"Plug-and-play" setup, intuitive scanning

Enables rapid deployment and immediate use without formal training, allowing new and experienced employees to immediately help improve operational efficiency

Multiple interfaces

Provides investment protection by permitting migration to new hosts without replacing scanners

Universal cables

Lowers total cost of ownership through easy replacement or upgrade; improved abrasion resistance in areas most likely to wear

Invest in a durable solution

Motorola is known worldwide for producing rugged, high-performance scanning devices. Advances in technology have allowed us to develop a widely affordable, durable scanner meeting our commitment to quality and performance. Built for long life in heavy day-to-day use, the Symbol LS9203 is equipped with internal shock mounts that enable it to withstand multiple drops onto concrete and comes with a stand that gives you more versatility and also extends the life of the scanner.

Eliminate worries with a full suite of services and support

Even the most durable products need a support plan. That's why Motorola covers every aspect of your mobility solution — from network design to ongoing

operations — providing unsurpassed breadth and depth of coverage to ensure all of your services and support needs are met. For the Symbol LS9203, Motorola offers two programs for replacement services beyond the standard warranty. Service from the Start – Bronze ensures three-day turnaround of a replacement unit, priority call response and escalation, as well as more comprehensive device coverage, including cosmetic repair and automatic application of engineering changes. Service from the Start – Advanced Exchange provides the same benefits as the Bronze program plus next business day delivery of a replacement unit.

For more information on the Symbol LS9203, please visit us on the Web at www.symbol.com/ls9203 or contact us at +1.800.722.6234 or +1.631.738.2400.

LS9203 Series Specifications

Physical Characteristics

Dimensions: (withstand)	5.51 in. H x 3.49 in. W x 2.96 in. D 14cm H x 8.86cm W x 7.52cm D
Dimensions: (withstand)	6.13 in. H x 3.93 in. W x 3.93 in. D 15.57cm H x 9.98cm W x 9.98cm D
Weight:	Scanner only: 9.9 oz./282g Withstand: 12.2 oz./379g
Power Source:	Dependent on host: • Host power • External power supply
Voltage:	5.0 VDC ± 10%
Nominal Current:	27 mA
Power:	1.4 watts
Mounting Options:	Fixed-mount stand
Color:	Twilight black

Performance Characteristics

Light Source:	650nm visible laser diode
Yaw Tolerance:	± 50°
Pitch Tolerance:	± 50°
Roll Tolerance:	0 to 360°
Print Contrast:	25% minimum reflectance difference
Scan Patterns:	Omni-directional; interlocking lines
Scan Rate:	1500 scans/second
Depth of Field:	0 to 8.5 in./0 to 21.6 cm @ 13 mil (100% UPC/EAN)
Nominal Working Range:	5 mil: (38%) 1 to 2.5 in./2.5 to 6.4 cm 7.8 mil: (60%) 0 to 6 in./0 to 15.2 cm 10.4 mil: (80%) 0 to 7.5 in./0 to 19 cm 13 mil: (100%) 0 to 8.5 in./0 to 21.6 cm

Width of Field:	1.6 in./40mm @ face 6.42 in./163mm @ 8.5 in.
Minimum Resolution:	5 mil
Decode Capability:	UPC/EAN/JAN/UPC/EANw/Supplementals, UCC/EAN128, Code 28, ISBT 128, Code 39, Trioptic Code 39, Interleaved of 5, Discrete of 5, Chinese of 5, Code 93, Code 1, Codabar/MSI, RSS 14, RSS Limited, RSS Expanded
Interface Supported:	USB S232, Keyboard Wedge and Wand
User Environment	
Operating Temp.:	32° to 104° F/0° to 40° C
Storage Temp.:	-40° to 158° F/-40° to 70° C
Humidity:	5% to 95% non-condensing
Ambient Light Immunity:	Immune to normal indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, incandescent, mercury vapor and sodium vapor (50ft-candle/4,844 lux) Sunlight (8,000ft-candle/86,111 lux)
Dropspec.:	Withstand repeated 1 ft./1.2m drop to concrete
Regulatory	
Electrical Safety:	Certified to UL 1950, CSA C22.2 No. 950
Laser Safety:	CDRH Class IIa Laser Product IEC 60825 Class 1 Laser Product Class IIa Laser Product void of long-term viewing of direct laser light
EMC	CISPRB, FCCB, EN60825

1 - Does not include cable

2 - Refer to 100% UPC barcode (80% contrast) located 8 in. (10cm) from the scanner nose

PlasticPrinters.com

To Order Contact:

Plasticprinters.com
sales@plasticprinters.com
1.800.808.7472

745 Spiral Blvd.
Hastings, MN 55033

